

Item no. 4450.T10

- Steel structure in compliance with UNI EN 10130, 1.5 mm thick. Rounded edges to avoid abrasion. Two holes on the rear for fixing to the wall.
- Door rebated on three sides; pull-resistant hinge side. Steel door back cover 2 mm thick. Knob with programmed breakage steel shaft: if forced, the knob will break before the mechanism. Illuminated display and menu as easy to use as a mobile phone. It accepts up to 2 user codes from 6 to 10 digits (up to 10 billion possible combinations). Emergency opening through a special profile key. Equipped with 2 keys.
- Steel made rotating deadbolts resistant to attack: 2 horizontal Ø 22 mm and 2 vertical Ø 22 mm.
- Temperature and humidity sensor inside the cabinet (an acoustic alarm, set by the user, warns of the possible formation of condensation to prevent oxidation of the metal parts of the weapons). Possibility of recording and updating hunted quantities for all existing species and to compare them with those of the previous year (for considerable orders, it would be possible to require writing on display in the desired language and the list of hunted species of the preferred country). 2 pre-set reminders: "Gun cleaning date" and "Licence renewal date" where only the date has to be entered. 4 Alphanumeric reminders set by the user (e.g. so the display provides a reminder of the date the hunting season opens). Easy insertion of the number of guns and rifles contained with relative ammunition. Audit trail of the last 50 operations in the memory to know who and when has opened the cabinet.

Capacity:

10 guns housing for item no. 4450.T10

Optional: On request:

the cabinet painted with a technique providing an elegant "wood colour" finish (add "**.L**" at the end of the item code).



Safety box for ammunitions/objects equipped with a Fai by Viro lock, supplied with 2 keys. Digital weather, can be positioned by the user as required, on the cabinet or elsewhere, which provides the following information: date and time; alarm clock; immediate temperature and humidity (with maximum and minimum values and alarm if they reach critical levels); weather forecasts and lunar calendar





Low consumption electronic board. Internal power supply (4 alkaline 1.5V batteries). On the display can be visualized the remaining battery level and estimated time left to replace the batteries. Non-volatile memory: the stored codes are not erased when power supply is removed. High concentration and scratch-proof polyethylene gun housing and rack (increased in thickness, that provides the perfect setting of single or double-barreled rifles, even with optical)

ITEM NO.	CAPACITY	EXTERNAL DIMENSIONS cm. H x W x D	INTERNAL DIMENSIONS cm. H x W x D	UNIT WEIGHT kg.	PACKING VOLUME m ³
4450.T10	10 guns housing	150 x 53.6 x 38	131 x 53.3 x 32.7	68.5	0.21