


- **Mechanism:**
  - brass pins; (except NUOVA MEZZA SFERA).
- **Packaging:**
  - single box.
  - All special executions are possible.

## NEW DOME PADLOCK - FASTENING UNIT

- **Keys:**
  - supplied with 2 Viro Top Security profile nickel-plated brass keys.
- **Mechanism:**
  - key removable in locked and unlocked position;
  - ball type locking;
  - mushroom brass counterpins, pick-resistant;
  - inox stainless steel pin springs.
- **Supplied with:**
  - galvanized steel floor anchoring device with “sprung dust” cover and brass fixed escutcheon;
  - painted steel bracket for fastening to the roller shutter;
  - galvanized steel nut and washer for locking to the roller shutter.
- **Cylinder:**
  - 7 pins brass cylinder.
- **Rotating plate:**
  - for cylinder protection, burglar-resistant, anti-drill, case-hardened, tempered, copper and nickel-plated steel.
- **Body and locking pin:**
  - one-piece, solid galvanized steel.
- **Casing:**
  - polished inox stainless steel outer casing.



## NEW DOME PADLOCK WITH FIXING ACCESSORIES

Item No.	Description	Keys Item No.	Unit weight g	Pcs. per pack No.
4221	NEW DOME Padlock complete with accessories	039.A	2520	1




## NEW DOME PADLOCK ACCESSORY

Item No.	Description	Keys Item No.	Unit weight g	Pcs. per pack No.
4221.500	NEW DOME Padlock	039.A	1330	1



## SPECIFIC ANCHORING DEVICE ACCESSORY FOR NEW DOME PADLOCK

Item No.	Description	Keys Item No.	Unit weight g	Pcs. per pack No.
2.0.4221.198.00.000	Brass floor anchoring device	-	530	1



## NEW CONDOR - FASTENING UNIT

- **Body:**  
one-piece, solid galvanized steel.
- **Dead-bolt:**  
Ø 12 mm case-hardened, tempered, copper, nickel and chrome-plated steel, rotating resistant to attack.  
Grip with programmed breakage dead-bolt head, to prevent the dead-bolt being pulled out.
- **Mechanism:**
  - set up for use with any 40 mm (30+10) long, European profile, half cylinder with universal or DIN cam;
  - galvanized steel cam for dead-bolt blocking.

- **Supplied with:**
  - brass floor anchoring device with "sprung dust" cover and brass device ring nut;
  - forged and galvanized steel loose locking ring;
  - steel plates and screws for locking to the roller shutter.

Patented profile versions .PV or .PB;  
Merchandise for NEW CONDOR.

- **On request:**
  - Viro half cylinder item 1.772;
  - Viro half cylinder item 975.1;
  - Viro NEW EURO-PRO half cylinder item 875.30.10;
  - Viro PALLADIUM half cylinder item 880.30.10;

(all special executions of the items listed above are possible; patented profile versions .PV or .PB are also available for items 1.772 and 880.30.10).

- galvanized steel accessory for installation of the NEW CONDOR on up and over garage doors (item 4218.0469).

- **Rotating plate:**  
for cylinder protection, burglar-resistant, anti-drill, case-hardened, tempered, copper and nickel-plated steel.

## NEW CONDOR

Item No.	Description	Keys Item No.	Unit weight g	Pcs. per pack No.
1.4218	NEW CONDOR	-	1800	1

**N.B. cylinder not provided.**

## ACCESSORIES

Item No.	Description	Keys Item No.	Unit weight g	Pcs. per pack No.
4218.0469	Accessory for installation on up and over doors	-	820	1

Item 4218.0469

## CONDOR - FASTENING UNIT

- **Body:**  
one-piece, solid galvanized steel.
- **Dead-bolt:**  
Ø 12 mm case-hardened, tempered, copper, nickel and chrome-plated steel, rotating resistant to attack.  
Grip with programmed breakage dead-bolt head, to prevent the dead-bolt being pulled out.
- **Keys:**  
supplied with 4 Viro Top Security profile nickel-plated brass keys
- **Mechanism:**
  - key removable in locked and unlocked position;
  - ball type locking;
  - brass counterpins;
  - phosphor bronze pin springs;
  - lock protected by weather proof cap.




- **Supplied with:**
  - brass floor anchoring device with "sprung dust" cover and brass device ring nut;
  - forged and galvanized steel loose locking ring;
  - steel plates and screws for locking to the roller shutter.


- **Cylinder:**  
7 pins, with case-hardened, tempered, copper and nickel-plated steel burglar-resistant anti-drill plate.

- **On request:**
  - galvanized steel accessory for installation of the CONDOR on up and over garage doors (item 4218.0469).



Rotating anti-drill plate, for cylinder protection.





## CONDOR

Item No.	Description	Keys Item No.	Unit weight g	Pcs. per pack No.
4218	CONDOR	037	2500	1

## SPARE PARTS

Item No.	Description	Keys Item No.	Unit weight g	Pcs. per pack No.
4218.0469	Accessory for installation on up and over doors	-	820	1

## ACCESSORIES

Item No.	Description	Keys Item No.	Unit weight g	Pcs. per pack No.
4718	Spare cylinder	037	270	1

## EAGLE - FASTENING UNIT FOR ROLLER SHUTTERS

### Installation:

on the jamb (with screws and tamper-proof balls supplied) at eye level, next to the roller shutter, as near as possible. The fixed end of the dead-bolt, in closed position, must remain inside the hole made on the roller shutter and be protected from the rubber seal. This way, the rotating ring remains between the EAGLE and the roller shutter.

### Body:

Round one-piece electropolished inox stainless steel, with 4 fixing points.

### Dead-bolt:

Ø 21 mm inox stainless steel. The part between the body and the roller shutter is protected by a case-hardened, tempered and galvanised rotating ring with a special black anticorrosion treatment. Pull opening and key insertion. 23 mm projection.

### Security cylinder:

7 pins, replaceable and re-keyable, even with the fastening unit installed. It is protected by a rotating burglar-resistant and anti-drill plate, made of 4.3 mm thick case-hardened, tempered and galvanized steel with a special black anti-corrosion treatment.

When the fastening unit is closed, the dead-bolt is fully housed in the body, pull-resistant.

### Keys:

supplied with 2 Viro Top Security profile nickel-plated brass keys with easy-to-handle grip. Versions available with high-security "PALLADIUM" cylinder and keys.

### Mechanism:


- push-to-close locking with key turning;
- mushroom brass counterpins, pick-resistant;
- inox stainless steel locking ring;
- inox stainless steel pin springs;
- inox stainless steel locking ring spring.
- sprung inox stainless steel pin, visible only when the dead-bolt is open, for removing and replacing the cylinder.

### Supplied with:

- tempered carbon steel, fixing screws (with Torx mark), to ensure easy and safe assembly on various construction materials (even concrete and masonry) without using plugs;
- inox stainless steel anti-tampering balls, to be used after installation to prevent access to the fixing screws head;
- black rubber seal, to protect the hole made on the roller shutter from scratches;
- drilling template.

## EAGLE

Item No.	Description	Keys Item No.	Unit weight g	Pcs. per pack No.
4217	EAGLE	039.A	1450	1
4217.4217	KA EAGLE pair	039.A	2900	1
4217.0601	EAGLE merchandiser	039.A	2410	1



## SPARE PARTS

Item No.	Description	Keys Item No.	Unit weight g	Pcs. per pack No.
4739	Spare cylinder	039.A	155	1



## ROLLER SHUTTER ACCESSORIES

### BRASS FLOOR ANCHORING DEVICE WITH "SPRUNG DUST" COVER - FORGED AND GALVANIZED STEEL RINGS - ANCHORING DEVICE BRASS RING NUT



Item No.	For items	Unit weight g	Pcs. per pack No.
<b>694</b>	4016 4116 4143 4153	730	1

### BRASS FLOOR ANCHORING DEVICE WITH "SPRUNG DUST" COVER - FORGED AND GALVANIZED STEEL RINGS - ANCHORING DEVICE BRASS RING NUT



Item No.	For items	Unit weight g	Pcs. per pack No.
<b>695</b>	107 4017 4117 4144 4154	1065	1

### FOR UP AND OVER DOORS - BRASS FLOOR ANCHORING DEVICE WITH "SPRUNG DUST" COVER - FORGED AND GALVANIZED STEEL ROOF-PLATE AND LOOSE PIN - ANCHORING DEVICE BRASS RING NUT



Item No.	For items	Unit weight g	Pcs. per pack No.
<b>696</b>	4017 4117 4144 4154	1825	1

### BRASS FLOOR ANCHORING DEVICE WITH "SPRUNG DUST" COVER - FORGED AND GALVANIZED STEEL ROOF-PLATE AND LOOSE RING - ANCHORING DEVICE BRASS RING NUT



Item No.	For items	Unit weight g	Pcs. per pack No.
<b>4219</b>	4015 4016 4017 4115 4116 4117 4143 4144 4153 4154	1825	1

## COMPONENTS

Item No.	Ring nut	Anchoring device and plug	Loose ring hole Ø mm 15	Fixed ring hole Ø mm 15	Loose pin	Roof-plate	
<b>694</b>	A	B	D	E	-	-	-
<b>695</b>	A	B	F	G	-	-	-
<b>696</b>	A	B	-	-	H	I	I
<b>4218</b>	A	B	D	-	-	CONDOR	CONDOR
<b>1.4218</b>	A	B	D	-	-	NEW CONDOR	NEW CONDOR

## ACCESSORIES

Item No.	Type
A 2.0.0694.065.00.000	A
B 2.8.0694.198.00.000	B
D 2.0.0694.057.00.117	D
E <b>694.590.117</b>	E
F 2.0.0695.057.00.117	F
I 2.0.0696.461.00.217	I

N.B. the anchoring device (B) is not suitable for item 4221 ("New Dome") which has its own device